

DoubleL



900 Series Conveyors




Double L

900 Series Conveyors

- Bearing Rollers Throughout
- Tapered Self-Cleaning Pulleys
- No-drop Design
- Best Mobility Conveyor



Conveyor Model	908	909	920	936	976	977	985
Width	6' 6" / 1.98 m	6' 6" / 1.98 m	7' 1" / 2.16 m	7' 7" / 2.31 m	6' 6" / 1.98 m	6' 6" / 1.98 m	7' 7" / 2.31 m
Length (extended)	25' / 7.62 m	40' / 12.19 m	60' 4" / 18.39 m	60' 4" / 18.39 m	25' / 7.62 m	40' / 12.19 m	85' / 25.91 m
Length (retracted)	25' / 7.62 m	40' / 12.19 m	35' 4" / 10.77 m	35' 4" / 10.77 m	25' / 7.62 m	40' / 12.19 m	45' / 13.72 m
Tires	8.40 x 12.0	8.40 x 12.0	6.70 x 15.0	6.70 x 15.0	6.70 x 16	6.70 x 17	6.70 x 15.0
Belt Width	30" / 76.2 cm	30" / 76.2 cm	30" / 76.2 cm	36" / 91.44 cm	36" / 91.44 cm	36" / 91.44 cm	36" / 91.44 cm
Discharge Height (min)	30" / 76.2 cm	30" / 76.2 cm	30" / 76.2 cm	30" / 76.2 cm	30" / 76.2 cm	30" / 76.2 cm	30" / 76.2 cm
Discharge Height (max)	44" / 111.76 cm	44" / 111.76 cm	44" / 111.76 cm	44" / 111.76 cm	44" / 111.76 cm	44" / 111.76 cm	44" / 111.76 cm
Capacity t/h	225 t / 204.12 MT	225 t / 204.12 MT	225 t / 204.12 MT	250 t / 226.8 MT	250 t / 226.8 MT	250 t / 226.8 MT	250 t / 226.8 MT
Horsepower	2 hp	3 hp	5 hp	7.5 hp	3 hp	5 hp	10 hp
Telescoping	no	no	yes	yes	no	no	yes



Please contact us for more information regarding our equipment at:

Double L
 PO Box 597
 2698 Lakeview Road
 American Falls, ID 83211
 U.S.A.

Phone: +1 208 226 5592
 Fax: +1 208 226 5934
 Email: sales@doublelinc.com



www.doublelinc.com