

DoubleL



9100 Series Conveyors



Double L

9100 Series Conveyors

- Trough-style, Overlapping
- Electric
- Adjustable dog-leg discharge allows for multiple conveyor angles.
- Inline gearboxes require less maintenance.



Please contact us for more information regarding our equipment at:

Double L
 PO Box 597
 2698 Lakeview Road
 American Falls, ID 83211
 U.S.A.

Phone: +1 208 226 5592

Fax: +1 208 226 5934

Email: sales@doublelinc.com

Conveyor Model	9134	9141	9143	9151
Width	6' 6" / 1.98 m	6' 6" / 1.98 m	6' 6" / 1.98 m	6' 6" / 1.98 m
Length	40' / 12.19 m	25' / 7.62 m	40' / 12.19 m	43', 67' / 13.12 m, 20.42 m
Tires	4.8 x 12.0	4.8 x 13	4.8 x 14	4.8 x 15, 6.7 x 15
Belt Width	36" / 91.44 cm	36" / 91.44 cm	36" / 91.44 cm	36", 42" / 106.68 cm, 91.44 cm
Discharge Height (Min.)	35" / 88.9 cm	35" / 88.9 cm	35" / 88.9 cm	35" / 88.9 cm
Discharge Height (Max.)	49" / 124.46 cm	49" / 124.46 cm	49" / 124.46 cm	49" / 124.46 cm
Capacity t/hr	250 t / 226.8 MT	250 t / 226.8 MT	250 t / 226.8 MT	250 t / 226.8 MT
Horsepower	5 hp	5 hp	7.5 hp	5 hp
Telescoping	no	no	no	yes

Double L
www.doublelinc.com